



Product number	DIN/ISO Chain No.	Type	P	d1 max	b1 min	d2 max	L max	Lc max	h2 max	t/T max	Pt	Q min	Q0	q
			Pitch	Roller diameter	Width between inner plates	Pin diameter	Pin length	Pin length	Inner plate depth	Plate thickness	Transverse pitch	Standard average tensile stren	HØYER average tensile strength	Weight per meter
			mm	mm	mm	mm	mm	mm	mm	mm	mm	kn/LB	kn	kg/m
0600081004	C08B1	Simplex	12.70	8.51	7.75	4.45	16.70	18.20	11.80	1.60	-	18.0/4091	19.50	0.80
0600082003	C08B2	Duplex	12.70	8.51	7.75	4.45	31.20	32.20	11.80	1.60	13.92	32.0/7273	38.70	1.45
0600083003	C08B3	Triplex	12.70	8.51	7.75	4.45	45.10	46.10	11.80	1.60	13.92	47.5/10795	57.80	2.10
0600101002	C10B1	Simplex	15.875	10.16	9.65	5.08	19.50	20.90	14.70	1.70	-	2.4/5091	27.90	1.06
0600102020	C10B2	Duplex	15.875	10.16	9.65	5.08	36.10	37.50	14.70	1.70	16.59	44.5/10114	57.80	2.00
0600111000	C12B1	Simplex	19.05	12.07	11.68	5.72	22.50	25.20	16.00	1.85	-	29.0/6591	32.20	1.32
0600112005	C12B2	Duplex	19.05	12.07	11.68	5.72	42.00	44.70	16.00	1.85	19.46	57.8/13136	66.10	2.62
0600113000	C12B3	Triplex	19.05	12.07	11.68	5.72	61.50	64.20	16.00	1.85	19.46	86.7/19705	101.80	3.89
0600151000	C16B1	Simplex	25.40	15.88	17.02	8.28	36.10	39.10	24.00	4.15/3.1	-	60.0/13636	72.80	3.08/3.49
0600151010	C16B1	Simplex	25.40	15.88	17.02	8.28	36.10	39.10	21.00	4.15/3.1	-	60.0/13636	72.80	3.08/3.49
0600151500	C16B2	Duplex	25.40	15.88	17.02	8.28	68.00	71.00	21.00	4.15/3.1	31.88	106.0/2409	133.00	6.10/6.92
0600152000	C16B2	Duplex	25.40	15.88	17.02	8.28	68.00	71.00	24.00	4.15/3.1	31.88	106.0/2409	133.00	6.10/6.92
0600191000	C20B1	Simplex	31.75	19.05	19.56	10.19	41.30	45.00	26.40	4.5/3.5	-	95.0/21591	106.70	4.16
0600241001	C24B1	Simplex	38.10	25.40	25.40	14.63	53.40	57.80	33.20	6.0/4.8	-	160.0/3636	178.00	7.47